

PRODUCT CATALOG

2021-2022

Quality control is vitally important to us. By handling

Quality control is vitally important to us. By handling everything but the manufacturing process, we are able to keep the cost reasonable, maintain our exclusive relationship with our customers and assure their complete satisfaction.



HIGH PERFORMANCE GREASES





OSSOLEX - 3

Grades SKUs Available

NLGI 3 10Kg / 5Kg / 3Kg / 2Kg

1Kg / 500 Gm

Product Description

OSSOL OSSOLEX -3 greases are multi-purpose high quality lithium soap based grease. It is formulated to provide added protection against rusting & water washout in general purpose automotive applications at moderate temperatures and loads.

OSSOLEX -3 shows excellent mechanical stability & resistance to drying or softening which prevents leak out of bearings and ensures long life. It has good low temperature fluidity & High dropping point helps in achieving high operating temperature range.

Recommended for use in lubrication of Automotive chassis components, wheel bearings, clutch bearings, universal joints of cars, trucks & other mobile equipments operating under moderate conditions.

OSSOLEX RUN

Grades SKUs Available
NLGI 3 7Kg / 5Kg / 3Kg / 1Kg



OSSOL OSSOLEX RUN is a premium quality grease manufactured from high quality base stocks & lithium soaps fortified with specifically selected high performance additives. It provides outstanding Anti-Oxidative and structural stability.

OSSOLEX RUN shows excellent load carrying capacity ensures protection against wear & tear. It provides exceptional sealing properties & protects against rust and corrosion. Good thermal stability ensures extended life.

Suitable for lubrication for Chassis components, general lubrication of axles, ball joints & others. Recommended for use in lubrication of Automotive wheel bearings in trucks & buses and other applications operating under moderate conditions for a greasing interval of 49000 Kms in moderate conditions.



OSSOLEX GEL

Grades SKUs Available

NLGI 2 5Kg / 3Kg / 2Kg / 1Kg / 500 Gm

Product Description

OSSOL OSSOLEX GEL is a premium quality Lithium soap based grease fortified with specifically selected high performance additives & selected base oil stocks to provide ultimate performance. It provides outstanding Anti-Oxidative and structural stability.

OSSOLEX GEL shows excellent load carrying capacity ensures protection against wear & tear. It provides exceptional sealing properties & protects against rust and corrosion. Good thermal stability ensures extended life.

Suitable for lubrication for Chassis components, general lubrication of axles, ball joints & others. Recommended for use in lubrication of Automotive wheel bearings in trucks & buses and other applications operating under moderate conditions for a greasing interval of 80000 Kms in moderate conditions.





HIGH PERFORMANCE GREASES





Grades

SKUs Available

NLGI 3

5Kg / 2Kg / 1Kg / 500Gm



Product Description

OSSOL OSSOLEX LIFE is a premium quality Lithium Complex soap based grease fortified with specifically selected high performance extreme pressure additives & selected base oil stocks to provide excellent structural stability, resistance to washout & impeccable wear & tear protection. OSSOLEX LIFE shows excellent load carrying capacity ensures protection against wear & tear. It provides exceptional sealing properties, Outstanding Anti-wear & Extreme pressure properties ensures extended bearing life under extreme load conditions.

Suitable for lubrication for Chassis components, general lubrication of axles, ball joints & others. Recommended for use in lubrication of Automotive wheel bearings in trucks & buses and other applications operating under moderate conditions for a greasing interval of 100000 Kms in moderate conditions.




Grades

SKUs Available

NLGI 2

5Kg / 2Kg / 1Kg / 500Gm





Suitable for lubrication for Heavy duty equipments in Automotive, Marine, Off-shore, mining, cement & Industrial Applications Recommended for use in lubrication of Heavy Automotive trucks & buses and other applications operating under moderate conditions for a greasing interval of 100000 + Kms in moderate conditions.





